	The State of the S	NEW!	
	TracPhone V7	TracPhone V3	
Service Provider	Interna 1455 N. Santa R (888) 98	Satellite Systems ational Dutton, Suite A. osa, CA 95401 39-8199 motesatellite.com	Service Provider
Service	KVH mini-VSAT Broadband Airtime	KVH mini-VSAT Broadband Airtime	Service
Service Coverage Area	Global	Global	Service Coverage Area
Maximum Downlink Rate (Shore-to- Ship)	2 Mbps	2 Mbps	Maximum Downlink Rate (Shore-to- Ship)
Maximum Uplink Rate (Ship-to- Shore)	1 Mbps	128 Kbps	Maximum Uplink Rate (Ship-to- Shore)
Billing Method	Speed-based or Metered	Metered	Billing Method
Typical Cost per MB transmitted (see rate sheet)	<\$1.00 USD	\$0.99 USD	Typical Cost per MB transmitted (see rate sheet)
Typical Cost per minute for Voice (see rate sheet)	\$0.05 USD (speed-based plans)	\$0.49 USD	Typical Cost per minute for Voice (see rate sheet)

¹ Maritime GSM Picocell phone service is an optional service.

² With Maritime GSM Picocell phone service.

³ Unless subject to in-country regulations.

⁴ 1-year parts warranty extension with system purchase and subscription to Inmarsat Airtime by KVH; some restrictions may apply, <u>click here</u> for details.

	The State of the S	NEW!	
	TracPhone V7	TracPhone V3	
Antenna Dome Standard Diameter x Height/Weight	26" x 27"/60 lbs (66 cm x 69 cm/27 kg)	15.5" x 17.5" / 25 lbs (39.4 cm x 44.5 cm / 11.3 kg)	Antenna Dome Standard Diameter x Height/Weight
Antenna Dome Alternate Diameter x Height/Weight	35" x 39"/97 lbs (89 cm x 99 cm/44 kg)	19" x 21" / 30 lbs (49 cm x 53 cm / 13.6 kg)	Antenna Dome Alternate Diameter x Height/Weight
Matching TracVision Antenna Available	Standard - M7, HD7 Alternate - M9	Standard - M3 Alternate - M5	Matching TracVision Antenna Available
Voice	KVH "Enhanced Voice" Service or Maritime GSM Service ¹	KVH "Enhanced Voice" Service	Voice
Fax	Group 3 fax	Group 3 fax	Fax
Streaming Data	N/A	N/A	Streaming Data
SMS	Standard 3G (up to 160 characters) ²	N/A	SMS
Antenna Operating Temperature	-13°F to +131°F (-25°C to +55°C)	-13°F to +131°F (-25°C to +55°C)	Antenna Operating Temperature
Antenna Storage Temperature	-30°F to +160°F (-34°F to +71°C)	-30°F to +160°F (-34°F to +71°C)	Antenna Storage Temperature
Power	90-240 VAC	90-240 VAC	Power
GMDSS Approved	No	No	GMDSS Approved
Certification	Complies with EC directive 1999/5/EC RTTE, per compliance with EC directive 2006/95/EC, EMC directive 2004/108/EC and IEC 301-427; Compliant to FCC requirements	Complies with EC directive 1999/5/EC RTTE, per compliance with EC directive 2006/95/EC, EMC directive 2004/108/EC and IEC 301-427; Compliant to FCC requirements	Certification

¹ Maritime GSM Picocell phone service is an optional service.

 $^{^{\}rm 2}\,\rm With$ Maritime GSM Picocell phone service.

³ Unless subject to in-country regulations.

⁴ 1-year parts warranty extension with system purchase and subscription to Inmarsat Airtime by KVH; some restrictions may apply, <u>click here</u> for details.

	The Control of the Co	NEW!	
	TracPhone V7	TracPhone V3	
Warranty	2 Year Parts; 1 Year Labor ³	2 Year Parts; 1 Year Labor ³	Warranty
	TracPhone V7	TracPhone V3	
	The Control of the Co	NEW!	

¹ Maritime GSM Picocell phone service is an optional service.

 $^{^{\}rm 2}\,\rm With$ Maritime GSM Picocell phone service.

 $^{^{\}rm 3}\, {\rm Unless}$ subject to in-country regulations.

⁴ 1-year parts warranty extension with system purchase and subscription to Inmarsat Airtime by KVH; some restrictions may apply, <u>click here</u> for details.